

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 92DL0M2040/WH

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	20	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 600 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	20,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-		If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,380 0,382
Parameters for directional light sources:				
Peak luminous intensity (cd)	455		Beam angle in degrees, or the range of beam angles that can be set	60
Parameters for LED and OLED light sources:				
R9 colour rendering index value	14		Survival factor	0,50
the lumen maintenance factor	0,95			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,80		Colour consistency in McAdam ellipses	3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)		If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,0		Stroboscopic effect metric (SVM)	0,0

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3803$ $y=0.3820$ / $u'=0.2230$ $v'=0.5038$
 CCT=4041K (Duv=0.0025) Dominant WL:Ld =577.6nm Purity=28.8%
 Ratio:R=18.2% G=77.7% B=4.1%; Peak WL:Lp=455.7nm FWHM=26.2nm
 Render Index:Ra=83.8
 R1 =82 R2 =92 R3 =96 R4 =80 R5 =82 R6 =88 R7 =86
 R8 =65 R9 =14 R10=80 R11=78 R12=60 R13=85 R14=98 R15=76

Photo Parameters:

Flux = 1607 lm Eff. : 78.97 lm/W Fe = 4.934 W

Electrical parameters:

V = 220.17 V I = 0.1054 A P = 20.34 W PF = 0.8767

WHITE:ANSI_4000K

Status: Integral T = 21 ms Ip = 47369 (72%)

Model:RDL0MCOB_20W
 Tester:Petya Marinova
 Temperature:25.3Deg
 Manufacturer:EVERFINE

Number:92DLOM2040/WH
 Date:2015-04-29 11:32
 Humidity:65.0%
 Remarks:VSHQ150129-GB1