

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 934FTL35WW/WH

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	35	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	3 150 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	34,1	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,438 0,402	
Parameters for directional light sources:				
Peak luminous intensity (cd)	602	Beam angle in degrees, or the range of beam angles that can be set	38	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,90			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,60	Colour consistency in McAdam ellipses	1	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) - : not applicable;

(b) - : not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4385$ $y=0.4028$ $u'=0.2522$ $v'=0.5211$
 $CCT=2963K$ (Duv=-0.0007) Dominant WL:Ld =583.2nm WL:Lc = --nm Purity=52.5%
 Ratio:R=23.0% G=74.4% B=2.6%; Peak WL:Lp=602.5nm FWHM=119.5nm
 Render Index:Ra=81.2

R1 =80	R2 =91	R3 =95	R4 =78	R5 =80	R6 =89	R7 =81
R8 =55	R9 =0	R10=80	R11=78	R12=71	R13=82	R14=98 R15=72

Photo Parameters:

Flux = 4670 lm Eff. : 136.64 lm/W Fe = 14.14 W

Electrical parameters:

V = 220.00 V I = 0.2440 A P = 34.18 W PF = 0.6367
 WHITE:ANSI_3000K

Status: Integral T = 9 ms Ip = 42785 (65%)

Model:TRACK LIGHTS FTL
 Tester:Atanas DAKOV
 Temperature:25.3Deg
 Manufacturer:ELMARK

Number:934FTL35WW WH
 Date:2021-04-08 13:34:12
 Humidity:65.0%
 Remarks:7456