## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

## Model identifier: 955LED101T/WH

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	Integrated LED		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
• ·	nption in on- 00 h), rounded st integer	9	Energy efficiency class	G		
indicating if it rain a sphere (30	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	570 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode p expressed in W	oower (P <sub>on</sub> ),	8,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	83		
Outer	Height	600	Spectral power	See image		
dimensions without	Width	150	distribution in the	in last page		
	Depth	150				
	I	I		Page 1		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power <sup>(a)</sup>	-	lf yes, equivalent power (W)	-				
		Chromaticity coordinates (x and y)	0,321 0,353				
Parameters for directional light sources:							
Peak luminous intensity (cd)	451	Beam angle in degrees, or the range of beam angles that can be set	45				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	9	Survival factor	0,00				
the lumen maintenance factor	0,00						

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

