

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 969LEDW12/WH

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	640 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power ( $P_{on}$ ), expressed in W	13,1	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,385 0,370	
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	446	Beam angle in degrees, or the range of beam angles that can be set	120	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	8	Survival factor	0,50	
the lumen maintenance factor	0,93			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,54	Colour consistency in McAdam ellipses	4	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,2	

(a) '-': not applicable;

(b) '-': not applicable;

## Spectrum Test Report



### Color Parameters:

Chromaticity Coordinate:  $x=0.3856$   $y=0.3703$   $u'=0.2312$   $v'=0.4995$   
 CCT=3809K (Duv=-0.0045) Dominant WL:Ld =582.4nm WL:Lc = --nm Purity=26.8%  
 Ratio:R=19.2% G=77.7% B=3.1%; Peak WL:Lp=446.9nm FWHM=23.5nm  
 Render Index:Ra=82.0

R1 =81	R2 =88	R3 =92	R4 =82	R5 =81	R6 =83	R7 =84
R8 =64	R9 =8	R10=71	R11=81	R12=67	R13=82	R14=96 R15=76

### Photo Parameters:

Flux = 643.8 lm Eff. : 49.02 lm/W Fe = 1.992 W

### Electrical parameters:

V = 220.12 V I = 0.1101 A P = 13.13 W PF = 0.5419

WHITE:ANSI\_4000K

Status: Integral T = 85 ms Ip = 50931 (78%)

Model:LED WALL LAMP  
 Tester:Atanas DAKOV  
 Temperature:25.3Deg  
 Manufacturer:ELMARK

Number:969LEDW/WH  
 Date:2020-04-14 11:23:28  
 Humidity:65.0%  
 Remarks:6407