

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 96GRF52/76012

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated COB		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	550 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	6,8	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,20
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	74
Outer dimensions without separate control gear, lighting control	Height	190	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	75	
	Depth	75	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,374 0,383
Parameters for directional light sources:			
Peak luminous intensity (cd)	453	Beam angle in degrees, or the range of beam angles that can be set	60
Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	0,50
the lumen maintenance factor	0,95		

(a): not applicable;

(b): not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3744$ $y=0.3832$ / $u'=0.2187$ $v'=0.5035$
 CCT=4210K (Duv=0.0048) Dominant WL:Ld =575.7nm WL:Lc = --nm Purity=27.4%
 Ratio:R=16.3% G=81.0% B=2.8%; Peak WL:Lp=453.0nm FWHM=24.1nm
 Render Index:Ra=74.6

R1 =72 R2 =80 R3 =87 R4 =73 R5 =71 R6 =72 R7 =85
 R8 =57 R9 =0 R10=52 R11=69 R12=42 R13=73 R14=92 R15=66

Photo Parameters:

Flux = 433.4 lm Eff. : 62.85 lm/W Fe = 1.260 W

Electrical parameters:

V = 12.263 V I = 0.5623 A P = 6.895 W PF = 1.000
 WHITE:ANSI_4000K

Status: Integral T = 109 ms Ip = 40936 (62%)

Model:LED OUTDOOR LIGHTING
 Tester:Atanas DAKOV
 Temperature:25.3Deg
 Manufacturer:ELMARK

Number:96GRF52/76012
 Date:2022-08-31 13:13:36
 Humidity:65.0%
 Remarks:8841