

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 96GRF54/209022W

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	20	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 128 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	17,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer dimensions without separate control gear, lighting control	Height	90	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	300	
	Depth	300	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,425 0,402
Parameters for directional light sources:			
Peak luminous intensity (cd)	759	Beam angle in degrees, or the range of beam angles that can be set	78
Parameters for LED and OLED light sources:			
R9 colour rendering index value	2	Survival factor	0,50
the lumen maintenance factor	0,95		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a) '-': not applicable;

(b) '-': not applicable;

Lightsource Test Report


Product Information

Product Category: 52
Submitted Unit: T

Product Number: JD-CD140C02

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.4257$ $y=0.4026$ $u(u')=0.2440$ $v=0.3461$ $v'=0.5191$
CCT: $T_c=3187K$ ($duv=0.00110$) Color Ratio: $R=0.202$ $G=0.777$ $B=0.021$
Peak Wavelength: 592nm Half Bandwidth: 118.2nm
Dominant Wavelength: 581.7nm Color Purity: 0.486
CRI: R_i : $R_a=81.8$
 $R1=82$ $R2=91$ $R3=97$ $R4=82$ $R5=83$ $R6=90$ $R7=82$ $R8=59$
 $R9=2$ $R10=81$ $R11=83$ $R12=73$ $R13=84$ $R14=99$ $R15=74$



Photometric Parameters

Luminous Flux: 1128.6 lm

Efficiency: 65.62 lm/W

Radiant Power: 2.786 W

Electric Parameters

Voltage: 220.00V

Current: 0.1401A

Power: 17.2W

Power Factor: 0.5580

Frequency: 49.99Hz

Test Information

Scan Range: 380nm~800nm:1nm Photometric Method: sphere-spectroradiometer
Stabilization Time: 0 Min Photometric Condition: Sphere diameter: 1.50m, 4 π
Max of Signal: 45362 (3363) CCD Integration Time: 482.75 ms

Condition: Tx:28.0'C, Ti:27.6'C, R.H.:60%
Test Lab:
Operator:

Test Device: Inventfine CMS-2
Test Time: 2022-07-09 16:59:11
Inspector: