

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 96GRFLED003/T1W

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	100 in Nar-row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	3,2	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,433 0,401	
Parameters for directional light sources:				
Peak luminous intensity (cd)	52	Beam angle in degrees, or the range of beam angles that can be set	102	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	3	Survival factor	0,50	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	4	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) '-': not applicable;

(b) '-': not applicable;

Lightsource Test Report

Product Information

Product Number: JD-SP17070-1

Submitted Unit: T

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.4339$ $y=0.4010$ $u(u')=0.2499$ $v=0.3465$ $v'=0.5197$

CCT: $T_c=3007K$ ($duv=-0.00083$)

Color Ratio: $R=0.230$ $G=0.746$ $B=0.024$

Peak Wavelength: 604nm

Half Bandwidth: 136.6nm

Dominant Wavelength: 602.3nm

Color Purity: 0.506

CRI: R_i : $R_a=80.9$

$R_1=83$

$R_2=90$

$R_3=77$

$R_4=84$

$R_5=83$

$R_6=89$

$R_7=84$

$R_8=64$

$R_9=3$

$R_{10}=78$


$R_{11}=84$

$R_{12}=73$

$R_{13}=84$

$R_{14}=88$

$R_{15}=76$



Photometric Parameters

Luminous Flux: 100.5 lm

Efficiency: 31.22 lm/W

Radiant Power: 0.286 W

Electric Parameters

Voltage: 220.00V

Current: 0.0265A

Power: 3.22W

Power Factor: 0.5220

Frequency: 49.99Hz

Test Information

Scan Range: 380nm~800nm:1nm Photometric Method: sphere-spectroradiometer

Stabilization Time: 0 Min

Photometric Condition: Sphere diameter: 1.50m, 4 π

Max of Signal: 48763 (4386)

CCD Integration Time: 5036.74 ms

Condition: Tx:25.3'C, Ti:25.5'C, R.H.:60%

Test Lab:

Operator:

Test Device: Inventfine CMS-2

Test Time: 2022-07-11 10:10:36

Inspector: