

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 96GRFLED0041

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	300 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power ( $P_{on}$ ), expressed in W	3,1	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85
Outer dimensions without	Height	205	Spectral power distribution in the See image in last page
	Width	95	
	Depth	65	

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,313 0,335
<b>Parameters for directional light sources:</b>			
Peak luminous intensity (cd)	455	Beam angle in degrees, or the range of beam angles that can be set	30
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	26	Survival factor	0,50
the lumen maintenance factor	0,93		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi$ 1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a) : not applicable;

(b) : not applicable;

### Spectrum Test Report



**Color Parameters:**

Chromaticity Coordinate:  $x=0.3130$   $y=0.3359$  /  $u'=0.1954$   $v'=0.4720$   
 CCT=6442K (Duv=0.0066) Dominant WL:Ld =493.3nm WL:Lc = --nm Purity=6.7%  
 Ratio:R=13.8% G=80.0% B=6.2% ; Peak WL:Lp=455.7nm FWHM=17.6nm  
 Render Index:Ra=85.8

R1 =85    R2 =93    R3 =95    R4 =81    R5 =83    R6 =87    R7 =88  
 R8 =73    R9 =26    R10=81    R11=81    R12=54    R13=88    R14=98    R15=80

**Photo Parameters:**

Flux = 296.1 lm    Eff. : 93.49 lm/W    Fe = 975.6 mW

**Electrical parameters:**

V = 220.06 V    I = 0.01515 A    P = 3.167 W PF = 0.9497

WHITE:ANSI\_6500K

Status: Integral T = 143 ms    Ip = 51222 (78%)

Model:LED WALL RECESSED FIXTURES	Number:96GRFLED0041
Tester:Atanas DAKOV	Date:2020-07-29 13:48:40
Temperature:25.3Deg	Humidity:65.0%
Manufacturer:ELMARK	Remarks:6709