

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 96LEDP15780

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LRF		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	10	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	600 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power ( $P_{on}$ ), expressed in W	9,2	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,384 0,383	
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	443	Beam angle in degrees, or the range of beam angles that can be set	60	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	15	Survival factor	0,50	
the lumen maintenance factor	0,93			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,80	Colour consistency in McAdam ellipses	0	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) - : not applicable;

(b) - : not applicable;

## Spectrum Test Report



### Color Parameters:

Chromaticity Coordinate:  $x=0.3845$   $y=0.3830$   $u'=0.2253$   $v'=0.5049$

CCT=3939K (Duv=0.0017) Dominant WL:  $\lambda_d = 578.4\text{nm}$  Purity=30.3%

Ratio: R=18.6% G=78.2% B=3.2%; Peak WL:  $\lambda_p = 443.8\text{nm}$  FWHM=21.1nm

Render Index:  $R_a = 83.6$

R1 =82	R2 =87	R3 =93	R4 =85	R5 =83	R6 =84	R7 =87
R8 =68	R9 =15	R10=71	R11=86	R12=69	R13=83	R14=96
						R15=76

### Photo Parameters:

Flux = 577.2 lm Eff. : 62.39 lm/W  $\Phi_e = 1.781\text{ W}$

### Electrical parameters:

V = 229.96 V I = 0.04772 A P = 9.252 W PF = 0.8431

WHITE: ANSI\_4000K

Status: Integral T = 79 ms  $I_p = 49181$  (75%)

Model: GRF157 LED/10W  
Tester: Petya Marinova  
Temperature: 25.3Deg  
Manufacturer: ELMARK

Number: 96LEDP15780  
Date: 2018-12-18 16:23  
Humidity: 65.0%  
Remarks: ESPL20181009\_5143