

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 96RAY10

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	13	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 300 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 500
On-mode power ( $P_{on}$ ), expressed in W	11,3	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	73
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-		If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,328 0,352
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	448		Beam angle in degrees, or the range of beam angles that can be set	100
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	0		Survival factor	0,50
the lumen maintenance factor	0,93			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,90		Colour consistency in McAdam ellipses	0
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)		If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,0		Stroboscopic effect metric (SVM)	0,0

(a) '-': not applicable;

(b) '-': not applicable;

### Spectrum Test Report



**Color Parameters:**

Chromaticity Coordinate:  $x=0.3288$   $y=0.3528$  /  $u'=0.2000$   $v'=0.4829$   
 CCT=5653K (Duv=0.0075) Dominant WL:Ld =541.1nm WL:Lc = --nm Purity=4.7%  
 Ratio:R=12.6% G=83.1% B=4.3% ; Peak WL:Lp=448.9nm FWHM=19.9nm  
 Render Index:Ra=73.1

R1 =68	R2 =79	R3 =88	R4 =72	R5 =71	R6 =72	R7 =82	
R8 =53	R9 =0	R10=51	R11=69	R12=49	R13=70	R14=93	R15=61

**Photo Parameters:**

Flux = 1328 lm Eff. : 117.60 lm/W Fe = 3.950 W

**Electrical parameters:**

V = 219.94 V I = 0.05604 A P = 11.30 W PF = 0.9165  
 WHITE:ANSI\_5700K

Status: Integral T = 40 ms Ip = 45683 (70%)

Model:LED INGROUND LAMP  
 Tester:Atanas DAKOV  
 Temperature:25.3Deg  
 Manufacturer:ELMARK

Number:96RAY10  
 Date:2020-08-03 14:25:15  
 Humidity:65.0%  
 Remarks:6709