

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 99LED607

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	240 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	2,8	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	25	
		Chromaticity coordinates (x and y)	0,435 0,404	
Parameters for directional light sources:				
Peak luminous intensity (cd)	603	Beam angle in degrees, or the range of beam angles that can be set	120	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	7	Survival factor	0,50	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,42	Colour consistency in McAdam ellipses	0	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	Yes ^(b)	If yes then replacement claim (W)	20	
Flicker metric (Pst LM)	0,6	Stroboscopic effect metric (SVM)	0,2	

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4369$ $y=0.4071$ $u'=0.2492$ $v'=0.5226$

CCT=3025K (Duv=0.0012) Dominant WL: $L_d = 582.3nm$ Purity=53.3%

Ratio: R=22.7% G=74.9% B=2.4%; Peak WL: $L_p = 602.5nm$ FWHM=131.8nm

Render Index: $R_a = 82.6$

R1 =81 R2 =90 R3 =97 R4 =81 R5 =81 R6 =88 R7 =84

R8 =59 R9 =6 R10=77 R11=81 R12=69 R13=83 R14=99 R15=73

Photo Parameters:

Flux = 220.6 lm Eff. : 76.09 lm/W $P_e = 665.6 mW$

Electrical parameters:

V = 220.25 V I = 0.03097 A P = 2.899 W PF = 0.4250

WHITE: ANSI_3000K

Status: Integral T = 136 ms $I_p = 48197$ (74%)

Model: LEDSMD PAR16/3W
Tester: Petya Marinova
Temperature: 25.3Deg
Manufacturer: ELMARK

Number: 99LED607
Date: 2015-06-03 13:02
Humidity: 65.0%
Remarks: 27Q39115015