

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 99LED609CW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	400 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power (P_{on}), expressed in W	6,4	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84
Outer dimensions without	Height	105	Spectral power distribution in the See image in last page
	Width	21	
	Depth	21	

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,326 0,348	
Parameters for directional light sources:				
Peak luminous intensity (cd)	449	Beam angle in degrees, or the range of beam angles that can be set	120	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	10	Survival factor	0,50	
the lumen maintenance factor	0,95			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ 1)	0,90	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,6	Stroboscopic effect metric (SVM)	0,2	

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3260$ $y=0.3487$ / $u'=0.1996$ $v'=0.4804$

CCT=5775K (Duv=0.0067) Dominant WL: $\lambda_d = 522.8\text{nm}$ Purity=3.1%

Ratio: R=14.2% G=80.4% B=5.5%; Peak WL: $\lambda_p = 449.9\text{nm}$ FWHM=30.4nm

Render Index: Ra=84.3

R1 =82	R2 =89	R3 =94	R4 =84	R5 =83	R6 =85	R7 =89	
R8 =69	R9 =10	R10=74	R11=83	R12=66	R13=84	R14=97	R15=76

Photo Parameters:

Flux = 344.4 lm Eff. : 53.31 lm/W Fe = 1.096 W

Electrical parameters:

V = 220.03 V I = 0.03119 A P = 6.460 W PF = 0.9414

WHITE: ANSI_5700K

Status: Integral T = 143 ms Ip = 51108 (78%)

Model: LED PANELS ROUND/6W
Tester: Petya Marinova
Temperature: 25.3Deg
Manufacturer: ELMARK

Number: 99LED609CW
Date: 2017-11-23 15:20
Humidity: 65.0%
Remarks: 017V038A_4095