

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 99LED610IP65E

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	10	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power ( $P_{on}$ ), expressed in W	11,8	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,373 0,377	
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	451	Beam angle in degrees, or the range of beam angles that can be set	120	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	8	Survival factor	0,50	
the lumen maintenance factor	0,93			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,20	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) - : not applicable;

(b) - : not applicable;

## Spectrum Test Report



### Color Parameters:

Chromaticity Coordinate:  $x=0.3734$   $y=0.3771$   $u'=0.2204$   $v'=0.5007$   
 CCT=4197K (Duv=0.0023) Dominant WL:Ld =577.0nm WL:Lc = --nm Purity=25.2%  
 Ratio:R=17.5% G=78.9% B=3.6% ; Peak WL:Lp=451.3nm FWHM=19.2nm  
 Render Index:Ra=82.4 AvgR=75.3 TM30:Rf=84 Rg=95 Lav=566.8nm

R1 =80	R2 =88	R3 =93	R4 =82	R5 =80	R6 =83	R7 =87
R8 =66	R9 =8	R10=71	R11=80	R12=58	R13=82	R14=96 R15=75

### Photo Parameters:

Flux = 1022 lm Eff. : 86.30 lm/W Fe = 3.100 W

### Electrical parameters:

V = 225.21 V I = 0.1932 A P = 11.84 W PF = 0.2721  
 WHITE:ANSI\_4000K

Status: Integral T = 55 ms Ip = 50475 (77%)

Model:LED PANEL ROUND  
 Tester:Atanas DAKOV  
 Temperature:25.3Deg  
 Manufacturer:ELMARK

Number:99LED610IP65  
 Date:2021-07-28 14:43:09  
 Humidity:65.0%  
 Remarks:7593