

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 99LED831HEW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	GU10		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	750 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	7,2	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	50	
		Chromaticity coordinates (x and y)	0,384 0,387	
Parameters for directional light sources:				
Peak luminous intensity (cd)	313	Beam angle in degrees, or the range of beam angles that can be set	103	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	2	Survival factor	0,50	
the lumen maintenance factor	0,95			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	4	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3849$ $y=0.3871$ $u'=0.2239$ $v'=0.5067$
 CCT=3959K (Duv=0.0035) Dominant WL: $\lambda_d = 577.5\text{nm}$ WL: $\lambda_c = \text{--nm}$ Purity=31.7%
 Ratio: R=18.1% G=78.0% B=3.9% ; Peak WL: $\lambda_p = 594.1\text{nm}$ FWHM=148.0nm
 Render Index: $R_a = 82.5$

R1 =80	R2 =90	R3 =96	R4 =79	R5 =80	R6 =87	R7 =85
R8 =61	R9 =2	R10=78	R11=79	R12=61	R13=83	R14=98
						R15=73

Photo Parameters:

Flux = 753.8 lm Eff. : 104.33 lm/W $\Phi_e = 2.255$ W

Electrical parameters:

V = 229.49 V I = 0.05643 A P = 7.225 W PF = 0.5580

WHITE:ANSI_4000K

Status: Integral T = 55 ms $I_p = 36014$ (55%)

Model:LED GU10
 Tester:Atanas DAKOV
 Temperature:25.3Deg
 Manufacturer:ELMARK

Number:99LED813HEW
 Date:2022-09-08 08:36:06
 Humidity:65.0%
 Remarks:8756