Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 99LED835W

Type of light source:

(or other electric interface) Mains or non-mains:	MLS	Connected light	No
Colour-tuneable light source:	No	source (CLS): Envelope:	
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
•.	nption in on- 00 h), rounded st integer	11	Energy efficiency class	E			
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	1 300 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	4 000			
On-mode pow pressed in W	ver (P _{on}), ex-	11,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
(P_{net}) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	83			
Outer dimen-	Height	105	Spectral power dis-	See image			
sions without	Width	60	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load	Page 1 /			

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	90				
		Chromaticity coordi- nates (x and y)	0,387 0,390				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	11	Survival factor	0,50				
the lumen maintenance factor	0,95						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	4				
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-				
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,2				

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

