

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 99LED853CW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	40	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	3 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power (P_{on}), expressed in W	40,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	207	
		Chromaticity coordinates (x and y)	0,322 0,349	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	2	Survival factor	0,40	
the lumen maintenance factor	0,90			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,70	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3223$ $y=0.3496$ $u'=0.1968$ $v'=0.4803$
 CCT=5937K (Duv=0.0089) Dominant WL: $\lambda_d = 512.7\text{nm}$ WL: $\lambda_c = \text{--nm}$ Purity=3.6%
 Ratio: R=13.6% G=81.3% B=5.1%; Peak WL: $\lambda_p = 448.9\text{nm}$ FWHM=20.3nm
 Render Index: $R_a = 82.4$

R1 =79	R2 =86	R3 =92	R4 =83	R5 =81	R6 =82	R7 =88
R8 =68	R9 =2	R10=68	R11=82	R12=61	R13=81	R14=96 R15=73

Photo Parameters:

Flux = 3904 lm Eff. : 92.27 lm/W $P_e = 12.27\text{ W}$

Electrical parameters:

V = 219.97 V I = 0.2662 A P = 42.31 W PF = 0.7224
 WHITE:OUT

Status: Integral T = 8 ms $I_p = 49970$ (76%)

Model: HIGH POWER LED LAMP
 Tester: Atanas DAKOV
 Temperature: 25.3Deg
 Manufacturer: ELMARK

Number: 99LED853CW
 Date: 2020-10-09 13:09:17
 Humidity: 65.0%
 Remarks: 6929