

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ELMARK

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 99LED935/W

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	14,7	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,384 0,377	
Parameters for directional light sources:				
Peak luminous intensity (cd)	367	Beam angle in degrees, or the range of beam angles that can be set	112	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	3	Survival factor	0,50	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	0	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3845$ $y=0.3775$ $u'=0.2275$ $v'=0.5025$

CCT=3897K(Duv=-0.0008) Dominant WL:Ld =579.9nm Purity=28.7%

Ratio:R=18.5% G=78.5% B=3.1%; Peak WL:Lp=443.8nm FWHM=23.6nm

Render Index:Ra=81.3

R1 =80	R2 =86	R3 =92	R4 =82	R5 =80	R6 =82	R7 =85
R8 =63	R9 =3	R10=68	R11=82	R12=67	R13=81	R14=96
						R15=73

Photo Parameters:

Flux = 980.1 lm Eff. : 66.69 lm/W Fe = 2.958 W

Electrical parameters:

V = 229.96 V I = 0.1138 A P = 14.70 W PF = 0.5617

WHITE:ANSI_4000K

Status: Integral T = 51 ms Ip = 56571 (86%)

Model: SUPER SLIM LED PANELS/15W
Tester: Petya Marinova
Temperature: 25.3Deg
Manufacturer: ELMARK

Number: 99LED935/W
Date: 2019-06-19 15:21
Humidity: 65.0%
Remarks: 018V053A_5742