

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 99LED971WW

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	353 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power ( $P_{on}$ ), expressed in W	6,5	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,20
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0,20	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,449 0,409	
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	118	Beam angle in degrees, or the range of beam angles that can be set	113	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	0	Survival factor	0,50	
the lumen maintenance factor	0,93			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,80	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) '-': not applicable;

(b) '-': not applicable;

## Spectrum Test Report



## Color Parameters:

Chromaticity Coordinate:  $x=0.4492$   $y=0.4056$   $u'=0.2578$   $v'=0.5238$ 

CCT=2817K(Duv=-0.0009) Dominant WL:Ld =583.9nm Purity=56.6%

Ratio:R=23.9% G=73.8% B=2.4%; Peak WL:Lp=604.1nm FWHM=112.6nm

Render Index:Ra=80.0

R1 =78	R2 =91	R3 =94	R4 =77	R5 =79	R6 =89	R7 =79	
R8 =53	R9 =0	R10=79	R11=76	R12=72	R13=81	R14=98	R15=70

## Photo Parameters:

Flux = 353.3 lm Eff. : 54.19 lm/W Fe = 1.059 W

## Electrical parameters:

V = 229.98 V I = 0.03180 A P = 6.519 W PF = 0.8914

WHITE:ANSI\_2700K

Status: Integral T = 66 ms Ip = 31736 (48%)

Model:LED PANEL ROUND/6W  
Tester:Petya Marinova  
Temperature:25.3Deg  
Manufacturer:ELMARK

Number:99LED971WW  
Date:2019-06-18 12:54  
Humidity:65.0%  
Remarks:W1119X007\_5535