

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 99LED973CWE

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters


Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	18	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 390 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power ( $P_{on}$ ), expressed in W	18,8	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85
Outer dimensions without	Height	Spectral power distribution in the	See image in last page
	Width		
	Depth		

separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,317 0,333	
<b>Parameters for directional light sources:</b>				
Peak luminous intensity (cd)	449	Beam angle in degrees, or the range of beam angles that can be set	120	
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	20	Survival factor	0,50	
the lumen maintenance factor	0,93			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,90	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) - : not applicable;

(b) - : not applicable;

## Spectrum Test Report



### Color Parameters:

Chromaticity Coordinate:  $x=0.3173$   $y=0.3339$   $u'=0.1992$   $v'=0.4716$

CCT=6230K(Duv=0.0034) Dominant WL:Ld =492.2nm Purity=5.4%

Ratio:R=14.0% G=80.5% B=5.5%; Peak WL:Lp=449.9nm FWHM=22.7nm

Render Index:Ra=85.2

R1 =84	R2 =89	R3 =91	R4 =86	R5 =85	R6 =84	R7 =90
R8 =74	R9 =20	R10=72	R11=85	R12=62	R13=85	R14=95 R15=80

### Photo Parameters:

Flux = 1391 lm Eff. : 73.73 lm/W Fe = 4.530 W

### Electrical parameters:

V = 230.01 V I = 0.08566 A P = 18.87 W PF = 0.9578

WHITE:ANSI\_6500K

Status: Integral T = 24 ms Ip = 58293 (89%)

Model:LED PANELS ROUND/18W  
Tester:Petya Marinova  
Temperature:25.3Deg  
Manufacturer:ELMARK

Number:99LED973CW  
Date:2019-04-12 13:46  
Humidity:65.0%  
Remarks:W1118X117-2\_5478