

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ELMARK

**Supplier's address:** ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

**Model identifier:** 99POMT30/WH

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power ( $P_{on}$ ), expressed in W	15,3	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without separate control gear, lighting control	Height	50	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	70	
	Depth	330	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,443 0,406
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	9	Survival factor	0,50
the lumen maintenance factor	0,95		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,90	Colour consistency in McAdam ellipses	4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,2

(a)-: not applicable;


(b)-: not applicable;

# LED Test Report

**Product Mark**

Product Type :  
 Temperature :65'C  
 Operator :admin  
 Remark :

Manufacturer :BOHUA  
 Humidity :65%  
 Test Date :2022-05-31 09:56:11



**Chroma Parameters**

Chro.Coor.:x=0.4432 y=0.4068 u=0.2534 v=0.3489 duv=0.0003  
 CCT: 2919K Dominant Wave.:583.1nm Purity:55.1%  
 Flux RGB Ratio:R=23.5%,G=75.2%,B=1.3% Peak Wave:603.7nm Half Width:127.0nm

**Rendering Index:Ra= 83.0**

R1 =81	R2 =90	R3 =97	R4 =82	R5 =82	R6 =89	R7 =83	R8 =60
R9 =9	R10=78	R11=83	R12=73	R13=83	R14=99	R15=74	

**Photo Parameters**

Flux:1687.61lm Effi.:110.1lm/W Radiant:12212.5mW Iv:0.0mcd  
 Efficiency:0.124 Effi Level:A+ (EU 874-2012)

**Ele. Parameters**

Voltage:U=230.100V Current:I=0.1740A  
 Power:P=15.32W Power Factor:PF=0.958

**Lamp Parameters**

Voltage:U=0.000V Current:I=0.0000A Power:P=0.00W  
 Power Factor:PF=1.000 Efficacy:0.0lm/W

**Instrument state**

Instrument:Hopoo HP8000 Integral Time: 44.185ms VPeak: 14746  
 VDark: 1357 Product ID: 201306373