

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: STELLAR

Supplier's address: ELMARK INDUSTRIES SC, bul.Dobrudja 2, 9300 Dobrich Dobrich, BG

Model identifier: 99XLED627CW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	Integrated LED		
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	24	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 800 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode power (P_{on}), expressed in W	23,1	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,20
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,20	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,314 0,336	
Parameters for directional light sources:				
Peak luminous intensity (cd)	657	Beam angle in degrees, or the range of beam angles that can be set	114	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	4	Survival factor	0,50	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a) '-': not applicable;

(b) '-': not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.3146$ $y=0.3366$ $u'=0.1963$ $v'=0.4726$
CCT=6354K (Duv=0.0061) Dominant WL:Ld =494.0nm WL:Lc = --nm Purity=6.1%
Ratio:R=13.2% G=81.3% B=5.5%; Peak WL:Lp=450.6nm FWHM=22.8nm
Render Index:Ra=82.6

R1 =80	R2 =87	R3 =91	R4 =82	R5 =81	R6 =82	R7 =88	
R8 =69	R9 =4	R10=69	R11=81	R12=59	R13=82	R14=96	R15=75

Photo Parameters:

Flux = 1995 lm Eff. : 86.16 lm/W Fe = 6.406 W

Electrical parameters:

V = 219.99 V I = 0.2100 A P = 23.16 W PF = 0.5012
WHITE:ANSI_6500K

Status: Integral T = 19 ms Ip = 50144 (77%)

Model:LED PANEL ROUND OM
Tester:Atanas DAKOV
Temperature:25.3Deg
Manufacturer:ELMARK

Number:99XLED627CW
Date:2021-03-16 10:04:24
Humidity:65.0%
Remarks:7455